



UPPER FORK



CBD20ZGA

2.0T Electric Jack Pallet



UPPER FORK

PARAMETERS & PERFORMANCE

CBD20ZGA

FEATURE

Model		CBD20ZGA
Load capacity	kg	2000
Load center	mm	600
Wheel base	mm	1227
Operating type		Stand

WHEELS

Wheels type		PU
Wheel quantity Driving wheel/Bearing wheel		1/2/4
Driving wheel size	mm	φ230×70
Bearing wheel size	mm	φ80×70(Double wheels)

DIMENSION

Min.fork lowered height	mm	85
Min.fork lifting height	mm	195
Max.lifting height	mm	110
Overall fork width	mm	685
Inside width between forks	mm	365
Fork length	mm	1150
Fork width	mm	160
Fork thickness	mm	55
Min frounf height	mm	30
Overall length	mm	1700
Overall width	mm	850
Overall height(With handle)	mm	1066/1420
Min.Turning radius	mm	1560
Min.Aisle width for pallets 800x1200	mm	2237
Min.Aisle width for pallets 1000x1200	mm	2362

PERFORMANCE

Travel speed(laden/unladen)	km/h	4.6/5.2
Lift speed(laden/unladen)	mm/s	36/35
Lowering speed(laden/unladen)	mm/s	34/31
Gradeability(laden/unladen)	%	4/6

ELECTRICAL CONFIGURATION

Drive motor	kw	1
Lift motor	kw	0.8
Battery voltage/capacity	V/Ah	48V/65Ah
Brake		Electromagnetic/Regenerative
Controller		Pre-expansion

WEIGHT

Battery weight	kg	56
Service weight without battery	kg	347